



HSF

NOTES:
 Rated Current:1.0AMP.
 Contact Resistance:20mΩ Max.
 Withstand Voltage:500V AC/DC
 Insulation Resistance:1000MΩ Min.
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:PA9T+33%G.F UL94V-0 BK



Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE±0.05)



Ordering Information

1320-12 XX XX S XXX C A XX

No. of Pins Per Row:02~50	Contact Plating	Pin Length	Insulator	Packing	Series No.
G0=Gold Flash	L=A+B+2.0	C=PA9T	A=Tray	01~99	
G3=10u"Gold	Std:057=5.7				
G4=15u"Gold	068=6.8				
G5=30u"Gold	078=7.8				
S0=Gold Flash/Tin					
S3=10u"Gold/Tin					
S4=15u"Gold/Tin					
S5=30u"Gold/Tin					
SN=Tin					
SM=Matte Tin					



Item	Pin Length	A	B	Mating
Standard	5.7	1.80	1.90	2321
	6.8	1.80	3.00	2334
	7.8	1.80	4.00	2344
Alternate				

OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
X.X ±0.40	William Chen	2018/01/17	UNIT	mm [inch]	1320-12XXXXXXXCXXX
X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
X.XXX ±0.15	APPROVE	DATE	SHEET	1/1	1.27 Pin Header, DUAL ROW, S/T, H=2.0
Angle ± 3'			PROJ.		Customer NO.
DIM TOL					

WCON
 Http: www.wcon.com
 WCON-Dongguan Tel: +86 769 85358920
 WCON-Kunshan Tel: +86 512 57468408
 Fax: +86 769 85358915
 Fax: +86 512 57468468
 E-mail: sales@wcon.com
 E-mail: salesks@wcon.com