

# HSF

NOTES:  
 Rated Current:1.0AMP.  
 Contact Resistance:20mΩ Max.  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:1000MΩ Min.  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:PA9T+33%G.F UL94V-O BK

## Ordering Information



1320-22 XX XX M XXX C R XX

No. of Pins Per Row:02~50	Contact Plating G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin SN=Tin SM=Matte Tin	Pin Length L=B+C+D+W/2	Insulator C=PA9T	Series No. 01-99
------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------	---------------------	---------------------

Packing  
 A=Tray  
 T=Tube  
 P=Tube+CAP  
 R=Tape&Reel+CAP




Item	Pin Length	W	D	B	E	Mating
Standard	--	5.50	0.10	1.90	--	2321
	--	5.50	0.10	3.00	--	2334
	--	5.50	0.10	4.00	--	2344
Alternate						

PIN(PerRow)	2-15P	16-30P	31-50P
M	0.10	0.15	0.18



## Recommended P.C.B Layout (Top Side)

(PCB BOARD TOLERANCE±0.05)



REV	DATE	MODIFICATION DESCRIPTION	CHANGE	ANGLE	DIM	TOL	APPROVE	DATE	PROJ.	SCALE	Fit	PART NO.
A4	2023/02/02	Add Flatness	△△				Du Ying	OPERATION	DATE	SCALE	Fit	PART NO. 1320-22XXXXMXXXCXXX △△
A3	2021/12/28	MODIFY CAP	△△				Du Ying	OPERATION	DATE	UNIT	mm [inch]	
A2	2018/01/17	MODIFY PART NO.	△△				William Chen	CHECK	DATE	SIZE	A4	TITLE: 1.27 Pin Header, DUAL ROW, SMT, DOUBLE PLASTIC, WITHOUT POST, H=2.0
A0	2012/03/22	NEW	-----					CHECK	DATE	SHEET	1/1	Customer NO.
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	ANGLE	DIM	TOL	APPROVE	DATE	PROJ.	SCALE	Fit	

**WCON**  
 Http: www.wcon.com  
 WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com  
 WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com