



HSF

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)

NOTES:
 Rated Current: 2.0AMP.
 Contact Resistance: 20mΩ Max.
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min.
 Operation Temperature: -40°C to +125°C(GOLD)
 -40°C to +105°C(TIN)
 Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA9T+33%G.F UL94V-0 BK





Ordering Information

1215-11 XX XX R XXX X 0 XX

A3 **A2** **A1** **A0**

No. of Pins	Contact Plating	Pin Length	Insulator	Packing	Series No.
02~40	G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin SN=Tin SM=Matte Tin	L=A+B+D+2.5 Standard: 100=10.0	C=PA9T	0=PE Bag T=Tube	01~99



Item	Pin Length	A	B	E	Mating
Standard	10.00	2.80	4.00	2.50	2240 2243 2263 2272
Alternate					

A3	2020/06/15	Modify Pin 02~40P	A3	Du Ying	OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
A2	2019/02/28	Modify	A2	Ding	x.X ± 0.40	Du Ying	2020/06/15	UNIT	mm	1215-11XXXXRXXXCOXX A1
A1	2018/01/18	Modify P/N	A1	-----	x.XX ± 0.25	CHECK	DATE	SIZE	A4	TITLE:
A0	2012/04/18	NEW	-----	-----	x.XXX ± 0.15	APPROVE	DATE	SHEET	1/1	PH2.00 SINGLE ROW 90° H=1.5 PLANE BENDING
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	-----	Angle ± 3°	APPROVE	DATE	PROJ.	Customer NO.	
					DIM TOL					

WCON
 Http: www.wcon.com
 WCON-Dongguan Tel: +86 769 85358920
 WCON-Kunshan Tel: +86 512 57468408
 Fax: +86 769 85358915
 Fax: +86 512 57468468
 E-mail: sales@wcon.com
 E-mail: salesks@wcon.com