



**PLUG AND RECEPTACLE MATED AFTER TIGHTENING GLAND NUT**

MJE04 P-32 04 R XX 01 W  
 P=POWER  
 32=3.2mm  
 4=4Circuits  
 R-Right Angle Type  
 W/CON LOGO  
 W/CON internal code  
 PLATING: G0=11" GOLD  
 G1=30" GOLD  
 G2=50" GOLD  
 G3=100" GOLD  
 G4=150" GOLD

- SPECIFICATION:**
1. RATED CURRENT: 7A MAX(PER CONTACT);
  2. VOLTAGE RATING: 200V AC(RMS) ;
  3. CONTACT RESISTANCE:  
INITIAL: 20MΩ MAX. FINAL: 30MΩ MAX;
  4. WITHSTAND VOLTAGE: 1500V AC;
  5. INSULATION RESISTANCE: 1000MΩ MIN;
  6. OPERATION TEMPERATURE: -20℃ TO +130℃;
  7. CONTACT MATERIAL: COPPER ALLOY;
  8. PLATING: AU OVER 30U" MIN NICKEL;
  9. INSULATOR MATERIAL: PPS, U194V-0 ;
  10. RECOMMENDED PROCESS:  
WAVE SOLDER/PEAK TEMPERATURE: 260±5 C.5S.
  11. NUT MATERIAL: COPPER ALLOY;
  12. ALL MATERIALS SHOULD BE COMPLIANT TO ROHS
  13. WATERPROOF : IP67(WHEN MATED);

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.	TITLE:	Customer NO.	W/CON-Dongguan	W/CON-Kunshan
0	2022.09.22	NEW		XX XX X.XXX	ANDY-XIE	2022.09.20	mm inch	A4	MJE04P-3204RXX01 (W)	3.2mmSERVO MOTOR 04 Series POWER RECEPTACLE R/A W/T NUT		Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com	Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: sales@wcon.com
OPERATION	XX	±0.40	CHECK	DATE	SCALE	FIT	PROJ.	1/1				Http: www.wcon.com	
ANGLE	± 3°	±0.15	APPROVE	DATE	SIZE	SHEET							

