


HSF



SPECIFICATIONS

Insulation Resistance: 5MΩ Min
 Contact Resistance: 3.0Ω Max
 Withstand Voltage: DC 300V, 10S
 The Cable Assembly Must 100% Test

CONNECT METHOD

P1	Color	P2
01	XXX	XX
02	XXX	XX
03	XXX	XX
XX	XXX	01

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 24~30AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

Ordering Information

C9120 - xx 02 xxx 401

No. of Pins: 02~30P Shape Style: 02=Both ends Process Length of Line

NO.	PART NO.	NAME	Specification	Q' TY	UNIT
⑤	WF2008-TPSN01	Terminal	PH2.00mm Phosphor Bronze Tin Terminal	xx	PCS
④	WF2008-HxxW01	Housing	PH2.00mm xxP White Housing	1	PCS
③	WF2001-TPSN01	Terminal	JST PH2.00mm Phosphor Bronze Tin Terminal	xx	PCS
②	WF2001-HxxW01	Housing	JST PH2.00mm xxP White Housing	1	PCS
①	Wxxxx-1xxx00001	WIRE	UL: xxxx, AWG: 24~30, Color: xx, Wire	xxxx	MM

					工程图 ENGINEERING	绘图 DRAW	BEN	09/09/24	SCALE	FREE	 维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD
					X.X	±0.30			UNIT	mm	
					X.XX	±0.20			SIZE	A4	
					X.XXX	±0.10			SHEET	1/1	
					Angle	± 2'			PROJ.	客户料号 Customer NO.	
A0	09/09/24	NEW			变更说明 MODIFICATION DESCRIPTION	变更 CHANGE	核准 APPROVE				料号 PART NO. C9120-xx02xxx401
版次 REV	日期 DATE										品名 TITLE: PH2.00 **P HSG TO PH2.00 **P HSG